USB 3.1 Type-C[™] to HDMI A Socket Converter

User Manual



Contents

1.0 INTRODUCTION 1
2.0 FEATURES 1
3.0 SPECIFICATIONS 1
4.0 PACKAGE CONTENTS 2
5.0 OPERATION 2
6.0 CONNECTION DIAGRAM 2

USB 3.1 Type-C[™] to HDMI Socket converter

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

This is a USB 3.1 Type C[™] to HDMI A Socket, designed for connecting HDTV & Monitor to host computer, the host computer can easily connect to the HDTV. Connecting the TV set with a HDMI cable which is contacted with the HDMI socket of this converter It can work on Mac book or Google new Chromebook Pixel or Asus Zen AiO and other USB 3.1 Type C[™] supported devices.

2.0 FEATURES

- Support USB 3.1Type C[™] Video output 4K*2K@30hz resolution
- Support USB 3.1Type C[™] Video output 4K*2K@60hz resolution
- NO driver needed
- ABS Housing Provide white, black two colors
- Aluminium Housing Provide gold, silver, grey space, three colors
- Slim Type ABS Housing Provide white, black two colors
- With 10cm Cable
- USB 3.1Type C[™] interfaces support plug and play, hot swap
- Easy to carry and use

3.0 SPECIFICATIONS

Item No.:	
ABS Housing HDMI1.4b 4K*2K@30hz	716092 716092S
ABS Slim Type HDMI 2.0 4K*2K@60hz	716145 716145S
Aluminium Housing 1.4b 4K*2K@30hz	716092V 716092D 719092X
Aluminium Housing 2.0 4K*2K@60hz	716147 716147D 716147X
Size(L*W*H)	
ABS Housing	200*45*15.2mm
ABS Slim Type housing	200*25*11.5mm
Aluminium Housing	200*38*13mm
Input/Output Connector	
Input port	USB 3.1Type C™ Male*1
Output port	HDMI A Socket
Warranty	
Limited Warranty	1 Year

Environmental	
Operating Temperature	0°C~45°C
Operating Humidity	10% ~ 85 % RH (no
	condensation)
Storage Temperature	-20℃~ 70℃
Storage Humidity	5% ~ 90 % RH (no condensation)
System requirements	Windows, MAC OSX, Google
	Chrome
Regulatory Approvals	
	FCC CE Certification
	RoHS 2.0 & REACH Compliant
Accessories Adapter	
User Manual	English Version

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

- 1) Connect the HDMI Socket to HDTV & Monitor
- 2) Connect the USB 3.1Type C[™] male port of this product to computer

6.0 CONNECTION DIAGRAM

